

**GUARANTEED CHARACTERISTICS OF XLPE INSULATED MEDIUM VOLTAGE CABLE****1x240/25mm² NA2XS(F)2Y 12/20(24)kV****GENERAL**

• Producer	:	VATAN KABLO / TURKEY
• Cable Code	:	NA2XS(F)2Y
• Applied Standards	:	VDE 0276-620; Part 10 Section C
• Voltage Rate (U ₀)	(kV) :	12
• Voltage Rate (U)	(kV) :	20
• Max Operating Voltage (U _m)	(kV) :	24

STRUCTURAL PROPERTIES**CONDUCTOR**

• Material	:	Aluminium
• Cross-Section Area	(mm ²) :	240
• Minimum number of wires in conductor	(No) :	30
• Type of Stranding	:	CIRCULAR COMPACTED
• Outer Diameter (Approx.)	(mm) :	18,30
• Number of Core	(No) :	1

CONDUCTOR SCREEN

• Material	:	Semiconductive XLPE
• Nominal Thickness	(mm) :	0,50
• Minimum Thickness	(mm) :	0,30
• Outer Diameter (Approx.)	(mm) :	19,30

INSULATION

• Material	:	XLPE (DIX8)
• Nominal Thickness	(mm) :	5,50
• Minimum Thickness	(mm) :	4,85
• Outer Diameter (Approx.)	(mm) :	30,30

INSULATION SCREEN

• Material	:	Semiconductive XLPE
• Nominal Thickness	(mm) :	0,50
• Minimum Thickness	(mm) :	0,30
• Outer Diameter (Approx.)	(mm) :	31,30
• Semi Conductive Tape	:	S.C. Swellable Tape
• Tape Thickness	(mm) :	0,30

METALLIC SCREEN

• Material	:	Copper
• Type	:	Wire&Tape
• Number & Diameter of Wires	(No x mm) :	53x0,80
• Thickness & Width of Copper Tape	(mm x mm) :	0,10x10
• Swellable Tape Thickness	(mm) :	0,30
• Outer Diameter (Approx.)	(mm) :	33,80
• Total Cross Section Area	(mm ²) :	25,00



GUARANTEED CHARACTERISTICS OF XLPE INSULATED MEDIUM VOLTAGE CABLE

1x240/25mm² NA2XS(F)2Y 12/20(24)kV

INNER SHEATH (Filler+Bedding)

• Filler Material	:	-
• Bedding Material	:	-
• Nominal Thickness (mm)	:	-
• Minimum Thickness (mm)	:	-

METALLIC ARMOUR

• Material	:	-
• Number & Diameter of Wires (No x mm)	:	-
• Thickness of Steel Tape (mm)	:	-
• Width of Steel Tape (mm)	:	-
• Binding Ratio (%)	:	-

OUTER SHEATH

• Material	:	PE (DMP2)
• Colour	:	Black
• Nominal Thickness (mm)	:	2,50
• Minimum Thickness (mm)	:	2,10

ELECTRICAL PROPERTIES

• Test Voltage of 5 Minute Duration (kV-rms)	:	42
• Impulse Test Voltage (kV-Peak)	:	125
• Continuous Current Carrying Capacity in Air at 30 °C (A)	:	496 ** / 581 ***
• Continuous Current Carrying Capacity in Ground at 20 °C (A)	:	417 ** / 455 ***

** Trefoil Formation, *** Flat Formation

Above current carrying capacities are calculated at the following laying conditions:

- Ambient Temperature of Air	30 °C
- Soil Temperature	20 °C
- Depth of Laying	0,8 m
- Thermal Resistivity of Soil	1,5 K m /W

• Inductance (mH/km)	:	0,345 ** / 0,391 ***
• Capacitance (µF/km)	:	0,308
• Insulation Resistance (MΩ.km)	:	71,79

• Dielectric Losses (at 90 °C, 3 phases) (W/km)	:	167,203
---	---	---------

• Max. Continuous Conductor Temperature (°C)	:	90
• Max. Conductor Temperature at Short Circuit Condition (°C)	:	250 (5 s max. duration)



GUARANTEED CHARACTERISTICS OF XLPE INSULATED MEDIUM VOLTAGE CABLE

1x240/25mm² NA2XS(F)2Y 12/20(24)kV

Maximum Short-Circuit Current

(Start Temperature 90 °C, End Temperature 250 °C)

• Duration of 5 seconds	(kA)	:	10,09
• Duration of 1 seconds	(kA)	:	22,56
• Duration of 0,5 seconds	(kA)	:	31,90

Maximum Short-Circuit Current at Metallic Screen

(Start Temperature 80 °C, End Temperature 200 °C)

• Duration of 1 seconds	(kA)	:	3,20
• Duration of 0,5 seconds	(kA)	:	4,53

Dielectric Loss Factor

• At 90 °C (Maximum Operating Temperature)		:	40x10 ⁻⁴
• Conductor Resistance at 20 °C	(Ω/km)	:	0,1250
• Conductor Resistance at 90 °C	(Ω/km)	:	0,1603
• Charging Current	(A/km)	:	1,16
• Partial Discharge (at 2 U ₀)	(pC)	:	5,00

OTHER PROPERTIES

• Outer Diameter of Cable (Approx.)	(mm)	:	39,40
• Minimum Bending Radius (During Installation)	(mm)	:	591
• Lowest Laying Temperature	(°C)	:	-20,00
• Weight of Cable (Approx.)	(kg/km)	:	1720
• Weight of Aluminium (Conductor) (Approx.)	(kg/km)	:	670
• Weight of Armour (Approx.)	(kg/km)	:	-

Drums

• Type		:	Wooden
• Flange (Wheel) Diameter	(mm)	:	2000
• Barrel Diameter	(mm)	:	1000
• Barrel Length	(mm)	:	1000
• Length of Cable	(m)	:	1000
• Gross Weight	(kg)	:	2080

"Note: Vatan Kablo may change design constructions provided it comply with original standards."

**VATAN KABLO METAL
END. VE TİC. A.Ş.**
Valimise OSB Mahallesi 111 Sokak No.: 4/1
Ergene/TEKİRDAĞ Ticaret Sicil No.: 848162
Tel.: 0 (282) 676 42 20 (5 Hat)
Mersis No.: 0924000826500016
Yenikapı Vergi Dairesi : 924 000 8265

DATE
17.09.2025

**XLPE Insulated, Longitudinally Sealed, PE Sheathed
Single-Core Cable with Aluminium Conductor**



DESCRIPTION

Application

They are used in cable ducts, outdoor and indoor installations, under ground where the short circuit levels are high and industrial areas fed by electrical energy. If cable gets water inside due to the mechanical damages, swellable tapes prevent the movement of the water.

Design

1. Aluminium Conductor
2. Conductor Screen
3. XLPE Insulation
4. Insulation Screen
5. Semi-Conductive Swellable Tape
6. Copper Wire and Tape Screen
7. Swellable Tape
8. PE Outer Sheath

