

CURVED SAFETY GLASS DOOR CABINETS

▶ floor mounting & surface mounting



Technical Characteristic

- Usage for installation of electrical instruments
- Easy and Fast Installation
- Wide Space for the Cabling
- Pre-Drilled Entries For an Easy Installation
- Tempered Glass Door
- Thickness is 1.20 mm
- Triangle Lock System

CPD Surface Distribution Cabinets

Code	Dimension (WxHxD)	DIN Rail Modules	Pack
CPD 6006020 !	600x600x200	-	1
CPD 6007520	600x750x200	-	1
CPD 6009020 !	600x900x200	-	1
CPD 6010520	600x1050x200	-	1
CPD 6012025	600x1200x250	-	1
CPD 6015025	600x1500x250	-	1
CPD 6018025 !	600x1800x250	-	1



Можност празниот ормар да се дополни со дополнителни додатоци(држачи, маски...).

Code	Dimension (WxHxD)	DIN Rail Modules	Pack
CPD 6006020 !	600x600x200	72M (24x3 rows)	1
CPD 6007520 !	600x750x200	96M (24x4 rows)	1
CPD 6009020	600x900x200	120M (24x5 rows)	1
CPD 6010520	600x1050x200	144M (24x6 rows)	1
CPD 6012025	600x1200x250	168M (24x7 rows)	1
CPD 6015025	600x1500x250	216M (24x9 rows)	1
CPD 6018025	600x1800x250	264M (24x11 rows)	1

