

FLEXIBLE SPIRALLED SHEATH

Technical Characteristic

- Flexible spiral
- Made of polyvinyl chloride (P-PVC)
- Reinforced with a spiral made of polyvinyl chloride (U-PVC)
- Choices for different colours
- Suitable for light mechanical loads
- Self extinguishing, flame retardant
- Conform to European IEC standards EN 606170-1



Flexible Spiralled Sheath - Grey

Code	Dimension (Ø)	Pack
CP 30010	Ø 10 mm.	30
CP 30012	Ø 12 mm.	30
CP 30014	Ø 14 mm.	30
CP 30016	Ø 16 mm.	30
CP 30020	Ø 20 mm.	30
CP 30022	Ø 22 mm.	30
CP 30025	Ø 25 mm.	30
CP 30030	Ø 30 mm.	30
CP 30032	Ø 32 mm.	30
CP 30038	Ø 38 mm.	30

Flexible Spiralled Sheath - Black

Code	Dimension (Ø)	Pack
CP 31010	Ø 10 mm.	30
CP 31012	Ø 12 mm.	30
CP 31014	Ø 14 mm.	30
CP 31016	Ø 16 mm.	30
CP 31020	Ø 20 mm.	30
CP 31022	Ø 22 mm.	30
CP 31025	Ø 25 mm.	30
CP 31030	Ø 30 mm.	30
CP 31032	Ø 32 mm.	30
CP 31038	Ø 38 mm.	30

Flexible Spiralled Sheath Glands

Code	Description	Pack
DX 54408	Ø 8 PG7	20
DX 54410	Ø 10 PG7	20
DX 54411	Ø 10 PG9	20
DX 54412	Ø 12 PG11	10
DX 54413	Ø 12 PG13,5	10
DX 54414	Ø 14 PG13,5	10
DX 54416	Ø 16 PG13,5	10
DX 54417	Ø 16 PG16	10
DX 54420	Ø 20 PG21	10
DX 54422	Ø 22 PG21	10
DX 54425	Ø 25 PG29	5
DX 54428	Ø 28 PG29	5
DX 54432	Ø 32 PG36	5
DX 54435	Ø 35 PG36	5