

# CURVED SAFETY GLASS DOOR CABINETS

flush mounting



## Technical Characteristic

- Usage for installation of electrical instruments
- Easy and Fast Installation
- Wide Space for the Cabling
- Pre-Drilled Entries For an Easy Installation
- Tempered Glass Door
- Thickness is 1.20 mm
- Triangle Lock System



### CPD Flush Mounting Distribution Cabinets with Mounting Plate

| Code            | Dimension<br>(WxHxD) | DIN Rail Modules | Pack |
|-----------------|----------------------|------------------|------|
| CPD 6006010 SAM | 600x600x100          | Mounting Plate   | 1    |
| CPD 6007510 SAM | 600x750x100          | Mounting Plate   | 1    |
| CPD 6009010 SAM | 600x900x100          | Mounting Plate   | 1    |
| CPD 6010510 SAM | 600x1050x100         | Mounting Plate   | 1    |



### CPD Flush Mounting Distribution Cabinets with Din Rail Accessory + Blank Cover H : 200mm

| Code             | Dimension<br>(WxHxD) | DIN Rail Modules   | Pack |
|------------------|----------------------|--------------------|------|
| CPD 6006010 SAPP | 600x600x100          | 66M (22x3 rows)    | 1    |
| CPD 6007510 SAPP | 600x750x100          | 88M (22x4 rows)    | 1    |
| CPD 6009010 SAPP | 600x900x100          | 110M (22x5 rows)   | 1    |
| CPD 6010510 SAPP | 600x1050x100         | 132M (22 x 6 rows) | 1    |



### CPD - Flush Mounting Distribution Cabinets - with Din Rail Accessory

| Code             | Dimension<br>(WxHxD) | DIN Rail Modules | Pack |
|------------------|----------------------|------------------|------|
| CPD 6006010 SAPS | 600x600x100          | 88M (22x4 rows)  | 1    |
| CPD 6007510 SAPS | 600x750x100          | 110M (22x5 rows) | 1    |
| CPD 6009010 SAPS | 600x900x100          | 132M (22x6 rows) | 1    |
| CPD 6010510 SAPS | 600x1050x100         | 154M (22x7 rows) | 1    |