

CURVED SAFETY GLASS DOOR CABINETS

floor mounting & surface mounting

Technical Characteristic	
 Usage for installation of electrical instruments Easy and Fast Installation 	

- and Fast Installation • Wide Space for the Cabling
- Pre-Drilled Entries For an Easy Installation
- Tempered Glass Door
- Thickness is 1.20 mm • Triangle Lock System

CPD Surface Distribution Cabinets with Mounting Plate

Code	Dimension ^(WxHxD)	DIN Rail Modules	Pack
CPD 6006020 SUM	600x600x200	Mounting Plate	1
CPD 6007520 SUM	600x750x200	Mounting Plate	1
CPD 6009020 SUM	600x900x200	Mounting Plate	1
CPD 6010520 SUM	600x1050x200	Mounting Plate	1
CPD 6012025 SUM	600x1200x250	Mounting Plate	1
CPD 6015025 SUM	600x1500x250	Mounting Plate	1
CPD 6018025 SUM	600x1800x250	Mounting Plate	1



Complementary Items

Code	Din Modules	Pack
CP 12011	Terminal Blocks - 24M	1
CP 12012	Terminal Blocks - 36M	1
CPD606024	24M Din Rail Kit - 150mm.Height	1
CPD606025	24M Din Rail Kit - 200mm.Height	1
CPD606034	Blank Module Cover - 150mm.Height	1
CPD606035	Blank Module Cover - 200mm.Height	1
CPD606034M	Mounting Plate for CP606034	1
CPD606035M	Mounting Plate for CP606035	1
CPD606044	Base Plate for Floor Installation – 20 cm	1
CPD606054	Base Plate for Floor Installation – 25cm	1
CPD606056	Cable Entry Plate with Brush Style – 25cm	1
CPD606046	Cable Entry Plate with Brush-Style – 20 cm	1
CPD606045	Metal Lock Set For CPD range	1











PE

CP 12012

CPD606024

CPD606034

CPD606034M

CPD606044

CPD606045

.....

CPD606046